

NuGen™ XL

RIGID CORE

Rigid.
Flexible.
Beautiful.

NuGen XL combines the best of both worlds. Rigid core flooring that is also more flexible, easy to install, and beautiful in any room.

Use in Any Room

Waterproof so it's safe to use in kitchens, bathrooms, or laundry rooms.

Install Immediately

No acclimation time required. Buy and install immediately after purchase.

Rigid Core

Overcomes subfloor imperfections and telegraphing, unlike traditional luxury vinyl tile.

Durable

Stands up to kids, pets, high heels and heavy furniture.

Fast and Easy to Install

NuGen XL's fast-locking click system ensures a low-cost, low-mess installation – even over existing floors! No power tools required.

Quiet Under Foot

The acoustical backing provides superior sound absorption and overall comfort.



ULTIMATE DURABILITY



WATERPROOF



CLEANS EASILY



EASY TO INSTALL



NO TEMPERATURE LIMITS

BLACK WALNUT | CASPER
270293005



Diamond W
A Tarkett Company

 **Tarkett**

NuGen™ XL



Pecan Flame
Claro
270293001




Teak Marado
Natural
270293002




Mineral Oak
Long Grain
270293003



Lacebark Elm
Wheat
270293004



Black Walnut
Casper
270293005




Black Walnut
Spiced
270293006




Pin Oak
Drift
270293007



Pin Oak
Muslin
270293008



English Walnut
Ginger
270293009



Village Oak
Chino
270293010

| Specifications | |
|-----------------------------------|---|
| Nominal Thickness | 0.177" (4.5 mm) |
| Wear Layer Thickness | 0.012" (0.3 mm) |
| IXPE Acoustical Backing | 1mm |
| Finish Edge | Square |
| Finish | Polyurethane |
| Material | Phthalate Free, 100% Virgin Material |
| Reusable Content | 100% Reclaimable |
| Scratch/Scuff/Abrasion Properties | Excellent |
| Dimensional Stability | ASTM F2199 Passes |
| Static Load Limit | ASTM F970 Passes |
| Residual Indentation | ASTM F1914 Passes (PSI Equivalent > 5,000 lbs.) |
| Slip Resistance | ASTM D2047 ≥ 0.5 SCOF |
| Fire | ASTM E648 ≥ .45 w/cm ² |
| Smoke | ASTM E662 ≤ 450 |
| Heat Stability | ASTM F1514 Δ E ≤ 8 |
| Light Stability | ASTM F1515 Δ E ≤ 8 |
| Staining | ASTM F925 Passes |
| Installation System | UniClic Locking System |
| FloorScore® Certification | Certified |
| Size | 7" x 60" (181mm x 1520mm) |
| Pieces per Carton | 10 Planks |
| Weight per Carton | Planks: 43.4 lbs. (19.68 kgs.) |
| Area per Carton | 29.614 sq. ft. (9.026 m ²) |
| Cartons per Pallet | 45 |

A Full Line of Accessories are Available!



Phthalate Free



Tarkett North America

30000 Aurora Road
Solon, OH 44139
USA: 1-877-TARKETT (1-877-827-5388)
Canada: 1-877-436-6267

www.tarkettna.com



Connect with us
@ TarkettHome

For more accurate color and pattern representation, we suggest you visit an authorized Tarkett dealer to view an actual product sample.