



Product Specifications / Technical Data

Item #:	ACX-501, 502, 503
Composition:	Phthalate-Free Polyvinyl Chloride
Construction:	Floating Click
Size (inches / mm):	5.9" x 29.5" (149.86mm x 749.3mm)
Total Thickness:	5.5mm
Wear Layer:	.5mm (20mil)
Finish:	G55 Max Ceramic Bead
Edges:	Color Infused Bevel
Sq.Ft. / Piece:	1.21
Sq.Ft. / Carton:	16.95
Pieces / Carton:	14
Cartons / Pallet:	60 (1,017 sq.ft.)
Pallets / 20' Container:	20 (20,340 sq.ft.)
Weight / Pallet (Lbs):	1,850
Limited Warranty:	Lifetime Residential 10 Year Commercial
TESTING	
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	51 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements
SUSTAINABILITY	
Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes