



Product Specifications / Technical Data

Item #:	GEN-827, 828, 829
Composition:	Phthalate-Free Polyvinyl Chloride
Construction:	Floating Click
Size (inches / mm):	8.98" x 59.84" (227.9mm x 1519.9mm)
Total Thickness:	5.5mm
Wear Layer:	.5mm (20mil)
Finish:	G55 Max Ceramic Bead
Edges:	Color Infused Bevel
Sq.Ft. / Piece:	3.73
Sq.Ft. / Carton:	22.38
Pieces / Carton:	6
Cartons / Pallet:	48 (1,074.24 sq.ft.)
Pallets / 20' Container:	21 (22,559.04 sq.ft.)
Weight / Pallet (Lbs):	2,026.64
Limited Warranty:	Lifetime Residential 10 Year Commercial
TESTING	
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	51 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements
SUSTAINABILITY	
Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes