



Product Specifications / Technical Data

Item #:	GEN-801, 802, 803
Composition:	Phthalate-Free Polyvinyl Chloride
Construction:	Floating Click
Size (inches / mm):	7.08" x 48.03" (179.8mm x 1219.9mm)
Total Thickness:	5.0mm
Wear Layer:	.5mm (20mil)
Finish:	G55 MAX Ceramic Bead
Edges:	Color Infused Bevel
Sq.Ft. / Piece:	2.36
Sq.Ft. / Carton:	23.64
Pieces / Carton:	10
Cartons / Pallet:	50 (1,182 sq.ft.)
Pallets / 20' Container:	20 (23,640 sq.ft.)
Weight / Pallet (Lbs):	1,894
Limited Warranty:	Lifetime Residential 10 Year Commercial

TESTING

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	51 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements

SUSTAINABILITY

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes