

(URBAN 28
REV. 10-10-22)

COMPOSITION	Virgin Vinyl – Phthalate Free
INSTALLATION	Glue down
AVAILABLE SIZES	Concrete & Solid Tile: 12" x 24" Wood & Abstract Plank: 7.08" x 47.24"
GAUGE	2.5mm (.100")
WEAR LAYER	28 mil
FINISH	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
CERTIFICATIONS	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
WARRANTY	Lifetime Residential / 20-Year Commercial
REFERENCE SPECIFICATIONS	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
RADIANT PANEL	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
STATIC LOAD LIMIT	ASTM-F-970 Meets & Exceeds Passing Requirements
SLIP RESISTANCE	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
PACKAGING	12" x 24" – 2 sq.ft./tile; 36 sq.ft./carton; 1,944 sq.ft./pallet; 54 cartons/pallet; 20 pallets/container 7.08" x 47.24" – 2.32 sq.ft./plank; 34.88 sq.ft./carton; 2,090.4 sq.ft./pallet; 60 cartons/pallet; 20 pallets/container
COUNTRY OF MANUFACTURE	United States of America