



**BIGGER.
BOLDER LOOK.**

9.3" Wide x 72" Length



Andrion



Canoe



Carnelian



Cool Beige



Crescent



Grandville



Copen Hills



Maison



Paxton



Sandy Bridge



Surf Coast



Townhouse

AQUAPROOF XL PREMIUM WATERPROOF FLOORS

Size	14mm x 9.3" x 72"
Wear Layer	AC4 (Class 32)
Texture	Embossed In Register (EIR)
Edge	Enhanced Water Repellent Bevel
Underlayment	2mm Premium Foam
Locking System	Uniclic (Angle Flat Tap)
Applications	Kitchen, Mudroom, Living Room, Bedroom, Bathroom, & Basement
Packing	27.9 sf/ctn
Warranty	Lifetime Structural Lifetime Residential 10 Years Light Commercial

*6mil vapor barrier required for all application installations.

BENEFITS



Waterproof Protection



NanoTek™ Finish



100% PVC Free



Easy Cleaning



Prevents Mold & Bacteria



Kid & Pet Safe

TESTING RESULTS

Description	Results
Micro-Scratch Resistance EN 16094:2012	MSR-B1
ASTM F970-17 - Static load resistance	0.14mm
ASTM E303 - Pendulum Slip Resistance: ASTM D5824-98	Pass, tested in wet conditions, .38 average DCOF Low Risk
<i>Delamination / Vacuum Pressure Method:</i> GB/T 18103-6.3.2	Pass, No Delamination
<i>Delamination / Impregnation Strip Method:</i> EN 13329 Abrasion Resistance:	Pass, No Delamination Pass, AC4 >4,000
Scratch Resistance ISO 1518-1:	No visible scratch on the surface
NALFA 3.1 Static Load:	>8 MPa; Class 4 Heavy Commercial Requirement
NALFA 3.2 Thickness Swell:	<1%; Greatly Exceeds Class 4, Heavy Commercial Requirement
ASTM F-2199 Dimensional Stability:	<0.001" / linear foot
ASTM E648 Critical Radiant Flux: ASTM F1515	Exceeds Class 1
<i>G155 UV Fade Resistance 400 Hours:</i>	Pass, No Visible Fade
NALFA 3.4 Cleanability Stain Resistance:	Exceeds Class 4 Heavy Commercial Requirement
NALFA 3.5 Large Ball Impact Resistance:	>1400mm; Class 4 Heavy Commercial Requirement
NALFA 3.6 Large Ball Impact Resistance:	>525mm; Class 4 Heavy Commercial Requirement
NALFA 3.9 Caster Chair:	Pass; Class 3 Commercial Requirement
NALFA 3.110 Surface Bonding:	1.47 N/mm, Class 3 Commercial Requirement
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 Delta E Requirement
ASTM E648 Flammability:	Pass, Exceeds Class A
ASTM E662-17 Specific Optical Density:	Pass; <200
Phthalate content test	Not detected (less than the detection limit)
Locking Strength ISO 24334 Long/Short Side Joint:	1043 (N)
NALFA Laminate Surface Swell Test - Assembled Joint:	No Change