

SPECIFICATIONS

Construction	WATERPROOF CORE
Finish	UV COATING
Style	BEVEL EDGE
Embossing	EMBOSSED IN REGISTER HAND SCRAPED
Thickness	8.0MM (6.5MM + 1.5MM PAD)
Wear Layer	20MIL (.5MM)
Size	8.87" X 60" 9.38" X 60"
SF Per Carton	22.12 SQ FT/BOX" 23.39 SQ FT/BOX"
Pieces Per Carton	6
Weight Per Carton	36.51 LBS 38.36 LBS
Cartons Per Pallet	56
Pallets per Container	19
Residential	LIFETIME
Commercial Warranty	10 YEAR

TRIMS AVAILABLE

Overlap Stair Nose
Flush Stair Nose
Square Flush Stair Nose
Quarter Round
Reducer
T-Mold
End Cap

S/N	Item	Test Standard	Test Result
1	Length	ASTM 2055	+/-1mm
2	Width	ASTM 2055	+/-0.15mm
3	Overall Thickness	ASTM F387	With pad:+/-0.008(0.2mm)
4	Wear Layer Thickness	ASTM F410	±0.02mm
5	Squareness/Straightness	ASTM 2055	≤0.25mm
6	Peel Resistance	ASTM D903	≥8kgf/50mm
7	Coating Adhesions	ASTM D3359	≥4B
8	Dimensional Stability	ASTM2199	≤0.25%
9	Curling After Exposure to Heat	ASTM2199	≤2.0mm
10	Critical Radiant Flux	ASTM E648	Class1
11	Resistance to Chemicals	ASTM F925	pass
12	Resistance to Heat	ASTM F1514	pass
13	Resistance to Light	ASTM F1515	pass
14	FLOORSCORE	/	pass
15	GREEN GUARD	/	pass
16	GREEN GUARD GOLD	/	pass